



JNR Load Cell Indicator

- Stainless Steel Enclosure
- High Visibility Display
- Output Options Available
- Wall / Bulkhead Mount

JNR features a stainless steel, splash proof sealed enclosure complete with mounting brackets suitable for industrial weighing applications.
 Basic weighing functions: full range zero, preset tare, tare, weigh count, peak.
 Power supply options include 110-250VAC, 11-30VDC or internal rechargeable battery.
 Output and communication options available: RS232C to printer or computer, 4-20mA or 0-10vdc analogue output, opto-isolated relay output.
 Wireless version available with transmitter or wireless load cell (enquire for details).

Power Supply Options	110-250 VAC 11-30 VDC Internal rechargeable battery
Input Range	0.5 to 3mV/V
Load Cell Excitation	5VDC (120mA max.)
Accuracy	±0.01% range
Display	6-digit 18mm LCD or LED
Thermal Stability	2ppm /°C
Dimensions	165 x 110 x 60 mm
Output Options:	
- Digital	RS232C
- Analogue	4-20mA / 0-10V
- Relay (opto-isolated)	1 or 2 rated 100mA @ 24V

Specifications subject to change without notice.

Force Logic UK Ltd
 N4 Lambs Farm Business Park
 Swallowfield
 Berkshire RG7 1PQ
 UK
 +44 (0)118 988 8807
 info@force-logic.co.uk www.force-logic.co.uk

Force

LOGIC UK
 Manufactured in the UK 